



IBM XIV Storage System

Storage Reinvented

Overview

The IBM XIV® Storage System is a ground-breaking, high-end disk system, designed to support business requirements for a highly available information infrastructure. Built from a grid of standard Intel®/Linux® components, it is connected in an any-to-any topology by means of massively paralleled, non-blocking Gigabit Ethernet.



IBM XIV applies automated data distribution, unique caching, and other innovations to eliminate hotspots and deliver single-tier storage featuring high-end performance, reliability, availability, and scalability, at exceptionally low Total Cost of Ownership (TCO). The XIV architecture can scale performance with capacity - no manual tuning required - thus enabling capacity growth without complexity.

IBM XIV comes in easily scalable partial-to-full racks configured with either 1 TB or 2 TB disk drives, and including full functional capabilities from the smallest configuration to the largest.

Physical features per rack

Disks

- Very High Density Slower Rotation (VHDSR) disk drives
- 7,200 RPM supported
- Capacity: 1 TB or 2 TB

Physical Specifications

- Dimensions: Height: 78.4 in/199.1 cm; Width: 23.6 in/60 cm; Depth: 45 in/114.2 cm
- Maximum weight: 1,949 lb/884 kg
- Clearance: Front: 47 in/120 cm; Rear: 39.4 in/100 cm

Power

- Input voltage: Nominal, 200-240 VAC, at 60A or 30A (+/- 10%)
- Redundant power feed
- Single-phase power feed

Operating Environment

- Temperature: 10-35°C
- Altitude: up to 7,000 ft/2,134 m
- Humidity: 25-80%, non-condensing

Capacity and Resources (per module)

- Cache-to-disk bandwidth: 240 Gbps
-



IBM XIV Configurations

# Modules	# Disks	Usable capacity* 1 TB/2 TB	Connectivity		Power usage 1 TB/2 TB			Internal (grid) switching (Gbps)	# CPUs		Memory (GB)
			FC ports	iSCSI ports	kVA (peak)	kVA (idle)	kBTU		Single	Dual**	
6	72	27/55	8	0	3.4/3.1	2.9/2.8	11.0	30	6	9	48
9	108	43/87	16	4	5.0/4.5	4.2/4.0	16.4	48	9	15	72
10	120	50/102	16	4	5.5/4.9	4.7/4.4	17.8	52	10	16	80
11	132	54/111	16	4	6.1/5.4	5.2/4.7	19.3	56	11	17	88
12	144	61/125	20	6	6.7/5.8	5.7/5.1	20.7	60	12	18	96
13	156	66/134	20	6	7.2/6.2	6.2/5.5	22.2	64	13	19	104
14	168	73/149	24	6	7.8/6.6	6.7/5.9	23.6	68	14	20	112
15	180	79/161	24	6	8.4/7.1	7.2/6.2	25.1	72	15	21	120

Functional specifications

Data Protection

- Active-active with N+1 redundancy on system components
- Non-disruptive hardware and firmware upgrades
- Asynchronous and synchronous remote mirroring
- Up to 16,000 differential snapshots—Instant create, restore. Writable and “snap on snap”
- Self-healing: Rapid rebuild time after disk and module failure

Features (fully bundled with system)

- Thin provisioning
- Data migration
- Storage management and LDAP authentication
- Native multi-path support

Host Connectivity

- Fibre Channel rates: 1 Gbps, 2 Gbps, 4 Gbps
- iSCSI over Gigabit Ethernet
- SCSI-3 protocol for both FC and iSCSI



© Copyright IBM Corporation 2010

IBM Systems and Technology Group
Route 100
Somers, New York 10589

Produced in the United States of America
April 2010
All Rights Reserved

IBM, the IBM logo, ibm.com and XIV are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at “Copyright and trademark information” at ibm.com/legal/copytrade.shtml.

Intel is a registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.



Please Recycle

For more information

To learn more about the [IBM XIV Storage System](#), contact your IBM representative or IBM Business Partner, or visit: www.xivstorage.com

Other company, product and service names may be trademarks or service marks of others.

* Usable capacity after factoring in disk space used by mirroring for redundancy, spares, and metadata

**Feature code 1101 provides interface modules containing dual CPUs